MPK-THG

SERVICE MANUAL

Ver. 1.2 2009.04



US Model Canadian Model AEP Model Chinese Model

SPECIFICATIONS

Material

Plastic (PC, ABS), Glass

Water-resistance

O-ring, Buckle

Pressure-resistance

To a depth of up to 40 m (132 feet) underwater

Switches that can be externally operated

Power, Shutter, Playback, Zoom (W/T), Shooting mode,

white balance, Flash, Macro, Image size

Dimensions

Approx. 134 x 94 x 38 mm (5 3/8 x 3 3/4 x 1 1/2 in.) (w/h/d) (excluding the projecting parts)

Mass

Approx. 260 g (9.2 oz.) (marine pack only)

Included items

Hand strap (1)

LCD hood (1)

Front attachment A (for DSC-T77) (1)*

Rear attachment A (for DSC-T77) (1)*

* Attached to the waterproof case at purchase.

Front attachment B (for DSC-T700) (1)

Rear attachment B (for DSC-T700) (1)

Grease (1)

O-ring (1)

Desiccant (two-pack) (1)

Spacer (1)

Set of printed documentation

Optional accessories

Arm kit VCT-MP1K

Underwater video light HVL-ML20M (must be used together with arm kit VCT-MP1K and "InfoLITHIUM" (M series) battery pack, (M series battery charger))

O-ring kit ACC-MP101



Design and specifications are subject to change without notice.

MAIN FEATURE

Useable at a depth of up to 40 m (132 feet) underwater.

- This marine pack MPK-THG is exclusively for use with the Sony Digital Still Camera DSC-T700/T77. (Digital Still Camera for this case is not available in all countries/regions.)
- This marine pack is waterproof so the digital still camera can be used in the rain, snow, at the beach, or underwater.
- Using the marine pack with the digital still camera setting to (Underwater) will enable you to record beautiful underwater images.

A loose or nipped O-ring, sand or dirt on the O-ring may cause water leaks under water.

Be sure to check the O-ring before use.

For details, read the O-ring Maintenance Manual.

MARINE PACK



SECTION 1 EXPLODED VIEWS

NOTE:

- -XX and -X mean standardized parts, so they may have some difference from the original one.
- Items marked "*" are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.
- The mechanical parts with no reference number in the exploded views are not supplied.
- Abbreviation
 CH: Chinese model
 CND: Canadian model

The marked "\(\Delta\)" are parts in relation to waterproof.


Replace these components with Sony parts.

Be sure to check up waterproof after repair.

the grease of the blue tube of the accessory. When using the

grease of the yellow tube and the grease of the other Inc.,

it hurts the O-ring and it causes the water leakage.




Ref. No.	Part No.	<u>Description</u>	<u>Remarks</u>	Ref. No.	Part No.	<u>Description</u>	<u>Remarks</u>
△ 1	4-115-566-01	O RING, MAIN (Note)		16	4-119-161-01	SHAFT (DIA. 2.5X55), BUCKLE	
2	4-115-547-01	ATTACHMENT (R-A)		17	4-115-553-01	PUSH BUTTON ()	
3	4-115-560-01	BUCKLE		18	4-115-535-01	SPRING, PUSH BUTTON	
4	4-119-159-01	SCREW (1.7X4 #0-3), TP		19	4-115-536-01	RETAINER, O RING	
5	4-119-160-01	SLIDER (C), BUCKLE		△ 20	3-099-234-01	O RING (P2-A) (Note)	
6	4-115-562-01	COVER, BUCKLE		21	4-115-551-01	PUSH BUTTON A (♠ • 🖽)	
7	4-115-564-01	SLIDER (B), BUCKLE		22		PUSH BUTTON B (🚈)	
8	4-115-565-01	SPRING, BUCKLE		23		PUSH BUTTON B (4)	
9	4-115-563-01	SLIDER (A), BUCKLE		24		PUSH BUTTON B (🎖)	
10	2-589-173-01	RING (DIA. 1.5), E		25	4-115-552-31	PUSH BUTTON B (🏭)	
11	4-115-555-01	LEVER (A), BUTTON		26	3-099-285-01	SHAFT, HINGE	
12	4-115-556-01	LEVER (B), BUTTON		27	4-115-550-01		
13	4-115-557-01	LEVER (C), BUTTON		* 28	3-209-949-01	LABEL, O RING CAUTION (US, CND,	AEP)
14	4-115-558-01	LEVER (D), BUTTON		* 28		LABEL, O RING CAUTION (CN) (CH)	,
15	4-115-559-01	LEVER (E), BUTTON		29	4-115-554-01	LEVER (PLAY), BUTTON	

Front Case Block

(See page 3)


1-2. FRONT CASE BLOCK




(Note) When putting grease the O-ring (Ref. No. 57, 66), always use the grease of the blue tube of the accessory. When using the grease of the yellow tube and the grease of the other Inc., it hurts the O-ring and it causes the water leakage.

Ref. No.	Part No.	<u>Description</u>	<u>Remarks</u>	Ref. No.	Part No.	<u>Description</u>	<u>Remarks</u>
51	4-115-518-01	PROTECTOR, FRONT CASE		67	4-115-530-01	SPRING (R), ZOOM	
52	3-099-238-01	TP2.6X8 (PLATE)		68	4-115-529-01	SPRING (L), ZOOM	
53	3-099-221-01	PLATE, TRIPOD SCREW		69	4-115-528-01	COVER, 200M	
54	X-2342-708-1	FRONT CASE ASSY (SERVICE)		70	4-115-526-01	SHAFT (B), ZOOM	
55	4-115-545-01	COVER, BUTTON					
				71	4-118-571-01	SCREW (1.7X3 #0-1), TP	
56	4-119-159-01	SCREW (1.7X4 #0-3), TP		72	4-115-524-01	REFLECTOR	
1 57 1 57	2-591-447-01	O RING (P4) (Note)		73	2-593-524-01	SCREW, TIP1.7X3 SPECIAL	
58	4-115-531-01	KNOB, ZOOM (WT)		74	4-115-546-01	ATTACHMENT (F-A)	
59	4-115-533-01	SHEET, ZOOM ADHESIVE		75	4-115-567-01	PACKING, DROP PROTECTION	
60	4-115-532-01	COVER, ZOOM KNOB					
				76	2-055-632-01	LABEL (CN), CAUTION (CH)	
61	4-115-544-01	SHAFT, SHUTTER LEVER		76	3-087-452-01	LABEL, CAUTION (US, CND, AEP)	
62	4-115-543-01	LEVER, SHUTTER		77	4-115-527-01	SLIDER, ZOOM	
63	4-115-534-01	PUCH BUTTON D (POWER)		78	4-115-525-01	SHAFT (A), ZOOM	
64	4-115-535-01	SPRING, PUCH BUTTON		79	2-589-173-01	RING (DIA. 1.5), E	
65	4-115-536-01	RETAINER, O RING					
				80	4-115-541-01	LEVER (SHUTTER), BUTTON	
 ∆ 66	3-099-234-01	O RING (P2-A) (Note)		81	4-115-542-01	LEVER (PW), BUTTON	


1-3. ACCESSORIES




Front attachment A (1) (ATTACHMENT F-A) (for DSC-T77) 4-115-546-01



Front attachment B (1) (ATTACHMENT F-B) (for DSC-T700) 4-115-548-01



Rear attachment A (1) (ATTACHMENT R-A) (for DSC-T77) 4-115-547-01




Rear attachment B (1) (ATTACHMENT R-B) (for DSC-T700) 4-115-549-01



Spacer (1) 3-941-348-01



Hand strap (1) 2-591-542-01



LCD hood (1) 3-273-528-01



LCD hood strap (1) 3-099-290-01



Grease (1) ▲ 2-582-620-01 (Note)

(Note)


to waterproof.



O-ring (1) 1 4-115-566-01 (Note)

When putting grease the O-ring (4-115-566-01), always use the grease of the blue tube of the accessory. When using the grease of the yellow tube and the grease of the other Inc., it hurts the

O-ring and it causes the water leakage.



Desiccant (two-pack) (1) 3-876-901-01

The marked "企" are parts in relation

Replace these components with Sony parts.

Be sure to check up waterproof after repair.

La \(\Delta\) marquée sont des pièces par rapport à imperméable à l'eau.

Ne les remplacer que par une pièce portant le numéro spécifié.

Soyez sûr de vérifier vers le haut d'imperméable à l'eau après la réparation.

Ref. No. Part No. Description **Remarks** 2-674-692-01 O RING MAINTENANCE MANUAL (JAPANESE, ENGLISH, FRENCH, GERMAN, ITALIAN, DUTCH, SPANISH, PORTUGUESE, SWEDISH, RUSSIAN, TRADITIONAL CHINESE, SIMPLIFIED CHINESE, KOREAN, ARABIC) 4-111-867-11 MANUAL, INSTRUCTION (ENGLISH, FRENCH, SPANISH) (US, CND, AEP) 4-111-867-21 MANUAL, INSTRUCTION (DUTCH, GERMAN, ITALIAN) (AEP) 4-111-867-31 MANUAL, INSTRUCTION (PORTUGUESE, SWEDISH, RUSSIAN) (AEP) 4-111-867-41 MANUAL, INSTRUCTION (TRADITIONAL CHINESE, SIMPLIFIED CHINESE, KOREAN, ARABIC) (AEP, CH)

MPK-THG

SONY®

SERVICE MANUAL

Ver. 1.2 2009.04

US Model Canadian Model AEP Model Chinese Model

SUPPLEMENT-2

File this supplement with the service manual. (09-008)

• Change of Repair Parts

: Points added portion.

SECTION 1 EXPLODED VIEWS

Page			Former		New
2	Ref. No. 5 6		Description SLIDER (C), BUCKLE COVER, BUCKLE	Ref. No. 5 6	<u>Description</u> SLIDER (C), BUCKLE COVER, BUCKLE
3			73 72		73 72 82
	54	X-2342-708-1	FRONT CASE ASSY (SERVICE)	54 82	FRONT CASE ASSY (SERVICE) SHEET, LIGHT INTERCEPTION

Reverse 985261213.pdf

Revision History

*: S.M. revised only top cover.

Ver.	Date	Hiotom.	Contents	S.M. Rev.	
ver.	Date	History	Contents	issued	
1.0	2008.08	Official Release		_	
1.1	2008.12	Supplement-1 (S1 DI08-311)	Change of Repair Parts	Yes*	
1.2	2009.04	Supplement-2	Change of Repair Parts	Yes*	
1.2	2007.04	(S2 09-008)	Replacement of the SUPPLEMENT-1 with	103.	
		(52 07 000)	the SUPPLEMENT-2.		
			Please discard the SUPPLEMENT-1.		
			Trease diseard the SOTT ELIVIERY 1.		